




Ducted PP Fume Hood



LED Display



Waterproof Socket



PP Sink
resistant to acid,
alkali and anti-corrosion



Water&Gas
Remote Control

ADVANTAGE

1. It is safer to use anti-corrosive water tap.
2. Microprocessor control system, LED display.
3. With memory function in case of power-failure.
4. Made of porcelain white PP, resistant to acid, alkali and anti-corrosion.
5. Front window which is made of thick transparent toughened glass maximize light and visibility inside the fume hood, providing a bright and open working environment.

TECHNICAL PARAMETERS

Model	FH1000(P)	FH1200(P)	FH1500(P)	FH1800(P)
External Size (W*D*H)	1047*800*2450mm	1247*800*2450mm	1547*800*2450mm	1847*800*2450 mm
Internal Size (W*D*H)	787*560*700mm	987*560*700mm	1287*560*700mm	1587*560*700 mm
Work Surface Height	820mm			
Max Opening	740mm			
Air Velocity	0.3~0.8m/s			
Noise	≤68dB			
Illuminating Lamp	LED lamp			
	12W*1	30W*1	30W*2	36W*2
Blower	Built-in PP centrifugal blower (2 blowers for FH1800(P) only); Speed adjustable			
Front Window	Resistant to acid and alkali, Manual, 5mm toughened glass, height adjustable			
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Consumption	330W	360W	360W	360W
Material	Main Body	Made of Porcelain white PP, thickness 8mm, resistant to strong acid, alkali and anti-corrosion		
	Work Table	Chemical resistant phenolic resin		
Standard Accessory	Illuminating lamp, Water tap, Gas tap, Water Sink, Base cabinet Waterproof socket*2, 4 meters PVC duct (2 Pcs of 4 meters PVC duct for FH1800(P) only), Diameter: 250mm, PP centrifugal blower pipe strap*2 (4 Pcs for FH1800(P) only)			
Optional Accessory	PP work table, epoxy resin board or ceramic board, Active carbon filter, Outer PVC centrifugal blower (only need to select when the duct more than 4m)			
Gross Weight	160kg	198kg	225kg	259kg
Package Size (W*D*H)	Main Body	1188*938*1612mm	1388*938*1612mm	1688*938*1612mm
	Base Cabinet	1188*888*1000mm	1388*888*1000mm	1688*888*1000mm